

Kalkulator przestrzeni dyskowej

	Group1	Group2	Group3	Group4
Camera / Encoder used	Flexidome IP H.264	Autodome IP H.264	Clinion IP H.264	720p Clinion
Number of above selected product used	58	2	13	14
Total number of cameras/channels	58	2	13	14
Total number of cameras/channels all groups	87			

VRM Storage Estimator

Only input value in Purple boxes

Video bandwidth	468	1776	468	2984	Kbit/s
Audio enabled?	No	No	No	No	
Metadata (I/A) enabled?	Yes	No	Yes	Yes	
Total bandwidth	618	1776	618	3134	Kbit/s
Total bandwidth	89				Mbit/s

Min Retention Time	30	30	30	30	days
--------------------	----	----	----	----	------

Quiet time / Alarm time: hours per day	6	0	6	6	Hours per day
Quiet time / Alarm time: Video bandwidth	1443	0	1443	6736	Kbit/s
Quiet time / Alarm time: Total bandwidth	1593	0	1593	6886	Kbit/s
Quiet time / Alarm time: reduction factor	139.44%	100.00%	139.44%	129.93%	

VRM downtime in days	1.00				days
----------------------	------	--	--	--	------

Net Storage requirement	16970.0	1204.4	3603.6	19321.7	GiB for all days
	16.57	1.18	3.71	18.87	TiB for all days
	41299.7				GiB for all days
	40.33				TiB for all days

iSCSI array used
Type of VRM server

FAS2020 XStage2 40x1000GB

Qty:

2

Qty: